

Magnetic Drilling Machines

SPECIFICATIONS

Model	EVOMAG28	EVOMAG42	JHMUSA5	REVR401
Motor	120v, 1,200 Watts	110v, 1,200 Watts	1,400 Watts	110V, 230V 1,100 Watts
Speed (No Load)	570 RPM	450 RPM	330/660 RPM	350-600 RPM
Maximum Twist Drill Diameter	1/2"	1/2"	3/4"	1/2"
Maximum Cutter Diameter	1-1/8"	1-5/8"	2-3/8"	1-1/2"
Maximum Cutting Depth	2"	2"	3"	2"
Cutter Shank Diameter	3/4" Weldon Shank	3/4" Weldon Shank	3/4" Weldon Shank	3/4" Weldon Shank
Magnetic Holding Power 3/8" plate	2,860 lbs.	2,860 lbs.	2,473 lbs.	1,653 lbs.
Weight	38 lbs.	26 lbs.	53 lbs.	32 lbs.
Dimensions	23" h x 8-7/8" w	25-3/4" h x 8-3/4" w	23-5/8" h x 8-1/2" w	20" h x 7" w

Machines shown without permanent safety guard for marketing purposes only.



EVOMAG28

Mag Drills Feature

- Coolant system with internal cutter lubrication
- Safety Chain
- Full safety guard system
- Carrying Case
- 3 Year Warranty



EVOMAG42



JHMUSA5



REVR401



Scan to view our Magnetic Drills on our website. 01/18

800.446.4402



ISO 9001 Quality